

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 January 2005 (20.01.2005)

PCT

(10) International Publication Number
WO 2005/005173 A1

(51) International Patent Classification⁷: **B60C 23/06**

(21) International Application Number:
PCT/EP2003/007283

(22) International Filing Date: 7 July 2003 (07.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **NIRA DYNAMICS AB** [SE/SE]; Teknikringen 1F, S-583 30 Linköping (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HALL, Peter** [SE/SE]; Fanjunkaregatan 126, S-582 16 Linköping (SE). **GUSTAVSSON, Tony** [SE/SE]; Gustavsbergsgatan 8, S-431 37 Mölndal (SE). **GUSTAVSSON, Fredrik**

[SE/SE]; Farskinnsvägen 19, S-586 66 Linköping (SE). **LINDSKOG, Peter** [SE/SE]; Bygdegatan 420, S-583 31 Linköping (SE). **FORSSELL, Urban** [SE/SE]; Farsaxvägen 49, S-586 66 Linköping (SE).


(74) Agents: **JACOBY, Georg et al.**; Samson & Partner, Widenmayerstr. 5, 80538 München (DE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: TIRE PRESSURE ESTIMATION



(57) Abstract: A method of estimating the occurrence of a specific tire pressure deviation between actual and nominal pressure values for one or a plurality of wheels (i) is provided. One or more wheel radius analysis measurement values (ΔR) are subsequently obtained from a wheel radius analysis component (104), wherein the wheel radius analysis measurement values (ΔR) are related to single wheel radius values (Δr_i) of which each is indicative of the wheel radius of a particular wheel (i). One or more wheel vibration data values (Δf_i) are subsequently obtained from a wheel vibration analysis component (102), wherein each of the wheel vibration data values (Δf_i) is indicative of a vibration phenomena in the time dependent behavior of the rotational velocity of a particular wheel (i). One or more tire pressure output values ($\eta_i, \Delta p_i$) are calculated on the basis of both the wheel radius analysis measurement values (ΔR) and the wheel vibration data values (Δf_i) wherein each tire pressure output value ($\eta_i, \Delta p_i$) is indicative of the specific tire pressure deviation for a particular wheel (i).



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*